

HATCO SERIES TRH, TK, TQ700 SERIES TOASTERS
 TQ300 FOR IRELAND & ENGLAND ONLY) REPLACEMENT OF
 (OAK) SELECTOR SWITCH NO. 02-19-021 WITH (E.G.O.) SWITCH NO 02-19-082

NOTE: DISCONNECT TOASTER FROM POWER SUPPLY.

1. REMOVE MANUAL ADVANCE KNOB.
2. REMOVE RIGHT SIDE PANEL.
3. REMOVE CONTROL KNOB FROM SELECTOR SWITCH.
4. REMOVE THE SCREWS HOLDING SWITCH TO CONTROL PANEL.
5. PULL EXISTING SELECTOR SWITCH OUT OF CONTROL PANEL.
 (DO NOT DISCONNECT WIRES AT THIS TIME).
6. PLACE NEW (E. G. O.) SELECTOR SWITCH SHAFT THROUGH HOLE
 FROM EXTERIOR OF TOASTER WITH ELECTRICAL TERMINALS FACING
 DOWNWARD AND USE AS A TEMPLATE, MARK MOUNTING SCREW HOLES.
7. USE A 3/16" DRILL BIT FOR NEW MOUNTING HOLES.
 NOTE: BE CAREFUL NOT TO DRILL INTO INTERNAL WIRES.
8. ALL WIRES MUST HAVE THE LUG'S CUT OFF.
 STRIP INSULATION BACK 1/4" FROM END.

NOTE: CHANGE ONE WIRE AT A TIME USING THE LIST BELOW.

9.	OLD (OAK) SWITCH =====	REPLACEMENT (EGO) SWITCH =====
	N	P2
	L1	P1
	3	4
	2	3
	4	1
	1	2

10. USING NEW DRILLED HOLES SECURE NEW SWITCH IN PLACE.
11. MAKE SURE THE SWITCH IS IN (OFF) (CENTER) POSITION,
 REPLACE CONTROL KNOB WITH LINE ON CENTER OF THE (OFF)
 POSITION ON CONTROL PLATE.
12. REINSTALL RIGHT SIDE PANEL AND MANUAL ADVANCE KNOB.
13. CONNECT POWER SUPPLY AND TEST.