

## SAVORY SPEED CONTROL INSTALLATION INSTRUCTIONS

### REPLACEMENT FOR SAVORY NO. 12425

11/96

12425 CAN BE INSTALLED ON ALL 208/240 VOLT TOASTERS  
EXCEPT MODEL BG-1T.

1. REMOVE THE ENTIRE SPEED CONTROL -- BOARD & POT.  
SAVE THE KNOB, ONE NUT & WASHER.
2. REMOVE THE #18035 RESISTOR.
3. DISCARD THE RESISTOR, SPEED CONTROL & POT.
4. INSTALL THE NEW POT. ON THE FRONT PANEL, INSURING THE  
PROPER SPACING BETWEEN THE PANEL & THE POT. CONNECTIONS.  
USE THE NUT & LOCK WASHER TO ACCOMPLISH THIS. ALIGN THE  
KNOB ACCORDING TO THE FRONT PANEL GRADUATIONS & ATTACH THE  
KNOB.
5. WIRE THE SAME AS THE OLD SPEED CONTROL, USING WIRE  
NUTS. THIS POT. IS NOT POLARIZED.
6. THIS CONTROL WILL GIVE THE CUSTOMER A BETTER SPEED  
CONTROL RANGE. IT DOES NOT HAVE ANY ADJUSTMENT FOR  
VOLTAGE.